



KÖSTER SD Protection and **Drainage Sheet 3-400**

Technical Data Sheet W 901 030

Issued: 2019-09-09

Three-layer, high quality backfill protection and drainage sheet with high compressive strength for KÖSTER waterproofing of building structures, 2 m x 15 m, 30 m²

Features

The tree-layer KÖSTER Protection and Drainage Sheet 3-400 is a high quality protection and drainage sheet made of a green HD-PE dimple sheet with a filter fleece made of polypropylene mounted to the front side and a blue gliding foil mounted to the back side. Via the space inside, accruing seepage water or retained seepage water can be drained safely to the drainage pipe. The sheet does not rot, it is resistant to impact and to roots, it retains its shape and is resistant to aggressive water and humic acid as well as against bacteria and fungi; it has no negative effects on drinking water and has a high compressive strength.

Technical Data

N/I	at	Δr	ıal	

HD-PE green dimpled membrane: fleece: blue gliding foil: PE-LD Application direction blue gliding foil Side facing construction member: protective fleece Side facing ground: Area weight approx. 950 g / m² Compressive strength approx. 400 kN / m² Dimple height approx. 8 mm Air volume between dimples approx. 5.5 I/m2 approx. 3.5 I/ (m x s) Water drainage capacity Temperature resistance - 30 °C to + 80 °C

Fields of Application

KÖSTER Protection and Drainage Sheet 3-400 is a high quality protection for horizontal and vertical areas of buildings and construction members with ground contact after the application of waterproofing according to the DIN EN 18533 with e. g. polymer-modified bitumen thick film sealants, cold self-adhesive bitumen membranes or rigid mineral slurries.

The pressure resistant KÖSTER Protection and Drainage Sheet 3-400 is used to pointedly drain the ground (prerequisite: non-cohesive soil) in the immediate vicinity of the building according to DIN 4095. The drainage is ensured by the functionality of the filter fleece which is attached to the filter body.

Application

KÖSTER Protection and Drainage Sheet 3-400 is placed loosely in front of the waterproofing. If the area to be protected is not higher than 1.90 m, then the sheet can be unrolled horizontally. In case of heights above 1.9 m, the sheet is cut to the desired length and installed with an overlap on the sides of at least 10 cm. In the overlapping area, lift up the fleece of the bottom sheet and place it on top of the upper sheet. This will prevent ground from penetrating into the sheet from the side. The upper edge of the sheet must reach at least 15 cm higher than the waterproofing layer. The sheet is fixed in position in this area using KÖSTER SD Fixing Elements. Max. distance between elements is 40 cm. The heads which are included in the delivery prevent the tearing out of the sheet. The lower end of the sheet is lead to the drainage and touches it. To protect KÖSTER SD Sheets from unwanted entry of soil, the KÖSTER SD Edge Profile is installed. If the sheet is placed on horizontal areas, a min. slope of 2% has to be observed. The backfill material should consist out of round gravel. Make sure that the backfill does not contain sharp edged aggregate.

Packaging

W 901 030 Rolle

Storage

Store the material cool and dry; it can be stored indefinitely.

Related products

neialeu producis	
KÖSTER Bitumen Primer	Prod. code W 110 010
KÖSTER Bitumen Emulsion	Prod. code W 190 030
KÖSTER 21	Prod. code W 210 020
KÖSTER CFR 1	Prod. code W 220 023
KÖSTER NB 1 Grey	Prod. code W 221 025
KÖSTER NB 2 White	Prod. code W 222 025
KÖSTER NB 1 Fast	Prod. code W 223 025
KÖSTER NB Elastic Grey	Prod. code W 233 033
KÖSTER NB Elastic White	Prod. code W 234 033
KÖSTER NB 4000	Prod. code W 236 025
KÖSTER KBE Liquid Film	Prod. code W 245
KÖSTER Bikuthan 2C	Prod. code W 250 028
KÖSTER Bikuthan 1C	Prod. code W 251
KÖSTER Deuxan 2C	Prod. code W 252 032
KÖSTER Deuxan Professional	Prod. code W 256 032
KÖSTER BS 1 Bitumen Paste	Prod. code W 501 005
KÖSTER Fix-Tape 10 ALU	Prod. code W 810 AL
KÖSTER Butyl Fix-Tape Fleece	Prod. code W 815 015 F
KÖSTER Fix-Tape 15 DS	Prod. code W 815 020 DS
KÖSTER KSK ALU 15	Prod. code W 815 096 AL
KÖSTER KSK SY 15	Prod. code W 815 105
KÖSTER SD Edge Profile	Prod. code W 970 001
KÖSTER SD Fixing Element	Prod. code W 971 001
KÖSTER Roofing Nails	Prod. code W 981 001

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.

KÖSTER BAUCHEMIE AG • Dieselstraße 1-10 • D-26607 Aurich • Tel. 04941/9709-0 • Fax -40 • info@koester.eu • www.koester.eu