



Primostar®

DECLARATION OF CONFORMITY

Manufacturer:

Primostar Tootmine OÜ
Männiku tee 104 A, 11216 Tallinn, Estonia

Authorized representative:

PRIMOSTAR OÜ
Männiku tee 104 A, 11216 Tallinn, Estonia

Product:

PRIMOSTAR® METAL SHEET WATERSTOP 125R, Art. NO. 0002-125R-M
PRIMOSTAR® METAL SHEET WATERSTOP 125L, Art. NO. 0001-125L-M
PRIMOSTAR® METAL SHEET WATERSTOP 175R, Art. NO. 0002-175R-M
Construction joint sheet with a polymer coating.

Areas of use:**PRIMOSTAR® METAL SHEET WATERSTOP 125R / 125L / 175R**

used for waterproofing construction joints against pressurized water in various underground reinforced concrete structures.
For example, wall-to-floor, wall-to-wall, floor slab-to-floor slab and wall-to-ceiling, in construction joint joints. The most common areas of use are underground parking lots, tanks, etc.

Technical data:

- Steel sheet: galvanized steel
- Steel sheet width: 125 mm / 175 mm
- Steel sheet thickness: 0.7 mm
- Element length: 2,5 m / 7,5 m
- Coating: polymer coating
- Steel sheet thickness with polymer coating: approx. 1.7 mm
- Color:
 - Polymer coating: dark gray
 - Galvanized steel mesh: metallic
- Temperature resistance: -35°C to +75°C
- Installation temperature: no restrictions
- Ensures water resistance up to 24 m (2.4 bar), officially tested at TalTech University - test no. N° 372-A/19
- Tested to water resistance 15 bar - test protocol no. 1/2024
- Technical-technological service life 50 years

Estonia, Tallinn, 20.07.2026

Indrek Uusalu
Primostar OÜ
CEO

