



Primostar®

DECLARATION OF CONFORMITY

Manufacturer:

Primostar Tootmine OÜ
Männiku tee 104 A, 11216 Tallinn, Estonia

Authorized representative:

PRIMOSTAR OÜ
Männiku tee 104 A, 11216 Tallinn, Estonia

Product:

PRIMOSTAR® METAL SHEET WATERSTOP UNIVERSAL R-L, Art. NO. 0010-065+20-M
PRIMOSTAR® METAL SHEET WATERSTOP UNIVERSAL R-L, Art. NO. 0010-125+20-M
PRIMOSTAR® METAL SHEET WATERSTOP UNIVERSAL R-L, Art. NO. 0010-155+20-M
Universal construction joint sheet with polymer coating

Areas of use:

PRIMOSTAR® METAL SHEET WATERSTOP UNIVERSAL R-L

is used for waterproofing construction joints against pressurized water in various underground reinforced concrete structures. Typical applications include wall-to-floor, wall-to-wall, slab-to-slab, and wall-to-ceiling construction joints. Common areas of use are underground parking garages, tanks, and similar structures.

Technical data:

- Steel sheet: galvanized steel
- Steel sheet width: 85; 145; 175 mm
- 20 mm bending strip on one edge
- Steel sheet thickness: 0.5 mm
- Element length: 7.5 m
- Coating: elastic polymer
- Thickness of steel sheet with polymer coating: approx. 1.0 - 1.2 mm
- Color:
 - Polymer coating: dark gray
 - Galvanized steel profile: metallic gray
- Temperature resistance: -35°C to +75°C
- Installation temperature: no restrictions
- Watertight up to 24 m (2.4 bar), officially tested by TalTech University – Test No. 372-A/19
- Tested for water resistance to 15 bar - test report no. 1/2024
- Technical-technological lifespan 50 years

Estonia, Tallinn, 20.07.2026

Indrek Uusalu
Primostar OÜ
CEO

