



Primostar®

DECLARATION OF CONFORMITY

Manufacturer:

Primostar Tootmine OÜ
Männiku tee 104 A, 11216 Tallinn, Estonia

Authorized representative:

PRIMOSTAR OÜ
Männiku tee 104 A, 11216 Tallinn, Estonia

Product:

PRIMOSTAR® FORMWORK WATERSTOP, Art. NO. 0005
Watertight construction joint element as a replacement for floor, wall or ceiling formwork.

Areas of use:

PRIMOSTAR® FORMWORK WATERSTOP

is used to complete the construction joints of reinforced cast-in-place concrete floor and wall structures as a hidden formwork that remains inside the structure, as well as as a waterproofing element in the same construction joint.

Technical data:

- Steel sheet: galvanized steel
- Steel sheet width: 150 mm
- Steel sheet thickness: 0.7 mm
- Element length: 2.2 m, 1.095 m
- Perforated trapezoidal profile width: depends on the thickness of the structure
- Coating: polymer coating
- Steel sheet thickness with polymer coating: approx. 1.2 mm
- Color:
 - Polymer coating: dark gray
 - Galvanized steel mesh: metallic
- Temperature resistance: -35°C to +75°C
- Installation temperature: no restrictions
- Ensures water resistance up to 24 m (2.4 bar), officially tested at TalTech University - test no. N° 372-A/19
- Tested to water resistance 15 bar - test protocol no. 1/2024
- Technical-technological service life 50 years

Estonia, Tallinn, 20.07.2026

Indrek Uusalu
Primostar OÜ
CEO

